

**17.0" Touch LCD monitor ( Model: MV1768T )**

<b>LCD Technology</b>	<p>Active matrix TFT color LCD</p> <ul style="list-style-type: none"> <li>⊙ 17" diagonal screen size</li> <li>⊙ 1280 x 1024 addressable pixels</li> <li>⊙ 0.264 mm x 0.264 mm Pixel Pitch</li> <li>⊙ 300 cd/m<sup>2</sup> ( typ. ) Brightness</li> <li>⊙ 800:1 ( typ. ) Contrast Ratio</li> <li>⊙ Tr+Tf: 5ms ( typ. )</li> <li>⊙ L/R=80°/80°, U/D=80° / 80° Viewing Angle</li> </ul>
<b>Touch Screen</b>	5 W Resistive / Capacitive Type with RS232 or USB interface connector
<b>Display Resolution</b>	1280 pixels (H) x 1024 lines (V)
<b>Active Display Area</b>	337.9(H) x 270.3 (V) mm
<b>Displayable Color</b>	16.7millions colors
<b>Horizontal Scan</b>	30kHz to 80kHz
<b>Vertical Refresh</b>	50 Hz to 75Hz
<b>Pixel Frequency</b>	110MHz
<b>Compatibility</b>	<ul style="list-style-type: none"> <li>⊙ IBM &amp; VESA VGA 640 x 350, 70 Hz</li> <li style="padding-left: 20px;">640 x 400, 70 Hz</li> <li style="padding-left: 20px;">720 x 400, 70 Hz</li> <li style="padding-left: 20px;">640 x 480, 60 Hz</li> <li>⊙ VESA VGA 640 x 480, 72/75 Hz</li> <li>⊙ VESA SVGA 800 x 600, 56/60/72/75 Hz</li> <li>⊙ VESA XGA 1024 x 768, 60/70/75 Hz</li> <li>⊙ VESA SXGA 1280 x 1024, 60/70/75 Hz</li> </ul>
<b>Input Signal</b>	Analog RGB 0.7 Vp-p
<b>Auto-adjustment</b>	Yes
<b>I/O Connectors</b>	<ul style="list-style-type: none"> <li>⊙ DC power in</li> <li>⊙ VGA in D-sub 15 pin</li> <li>⊙ RS232 or USB</li> <li>⊙ Audio in</li> </ul>
<b>User Controls</b>	<ul style="list-style-type: none"> <li>⊙ Power On/Off Button</li> <li>⊙ External Auto-Adjustment</li> <li>⊙ OSD Control items:</li> </ul>



Model: MV1768T

	Auto Tune, Auto Contrast, Brightness, Contrast, H Position, V Position, Detail Adjust, Color Temperature, OSD Setup, Image Setting, Recall
<b>Power Saving</b>	VESA DPMS standard ( 4 mode )
<b>Power Consumption</b>	36 watt ( max. ), < 3 watt ( stand by mode )
<b>Stand tilt</b>	( -5°~30° )
<b>Agency approval</b>	
<b>Environmental operating temperature</b>	0 °~50°C
<b>Humidity</b>	80% maximum
<b>Storage</b>	⊙ Temperature: -20°~60°C / -4°~140°F ⊙ Humidity: 95% maximum
<b>Carton Dimension ( H*W*D )</b>	485mm * 460mm * 255mm
<b>Dimension ( H*W*D )</b>	390mm * 395mm * 230mm
<b>Weight</b>	N.W. .5.3Kg      G.W. 6.8Kg

The specification of the product is for reference only. It might be changed without any notice.

---