



OP-070

Metal Openframe Touch Screen Display
Low Consumption Power
Contrast Increase

❖ Specification

LCD Type	7" Active Matrix , TFT
Aspect Ratio	5:3 Format
Resolution	WVGA (800x480)
Pixel Pitch	0.1905mm x 0.1905mm
Active Area	152.4x 91.4
Contrast Ratio	1000:1 (typ.)
Brightness	400 (cd/m ²)
View Angle (H/V)	160 / 160
Response Time	30ms. (typ.)
Backlight Type	LED Backlight
Input Signal	VGA / DVI-D (option)
Plug & Play (pnp.)	VESA DDC 2B
Display Control	Display On / Off , Adjustment , OSD Control
Power Input	DC 12 V Adapter
Power Consumption	8 watt (Max) < 1watt (Stand By Mode)
Operation Temperature	0° to 50°
Operation Humidity	80% (max)
Frame / VESA Mount	VESA 75 x 75 (Option)
Weight	N.W 1.3kgs / G.W 2.3kgs
Dimension	169.1 x 135.63 x 33

❖ Ordering Information

OP-070	7" Openframe Only
OPT-070R	7" Openframe + 5-W Resistive Touchscreen
OPT-070C	7" Openframe + Capacitive Touchscreen

❖ Accessories

12V DC Adapter , Power Cord , VGA Cable , USB Cable , Touch Driver



❖ Dimension

