

OP-173

Metal Openframe Touch Screen Display
Low Consumption Power
Contrast Increase

❖ Specification

LCD Type	17.3" Active Matrix , TFT
Aspect Ratio	16:9 Format
Resolution	1600X900(HD+)
Pixel Pitch	0.239mm x 0.239mm
Active Area	382.1X 214.9 mm
Contrast Ratio	500:1 (typ.)
Brightness	220 (cd/m ²)
View Angle (H/V)	90 / 50
Response Time	8ms. (typ.)
Backlight Type	LED Backlight
Input Signal	VGA / DVI-D (option)
Plug & Play (pnp.)	VESA DDC 2B
Display Control	Display On / Off , Adjustment , OSD Control
Power Input	DC 12 V Adapter
Power Consumption	12 watt (Max) < 1 watt (Stand By Mode)
Operation Temperature	0° to 50°
Operation Humidity	80% (max)
Frame / VESA Mount	VESA 100 x 100
Weight	N.W kgs / G.W kgs
Dimension	420.2 x 258.9 x 43

❖ Ordering Information

OP-173	17.3" Openframe Only
OPT-173R	17.3" Openframe + 5-W Resistive Touchscreen
OPT-173C	17.3" Openframe + Capacitive Touchscreen

❖ Accessories

12V DC Adapter , Power Cord , VGA Cable , USB Cable , Touch Driver



❖ Dimension

